

Mueller Europe supply air-conditioning and refrigeration tube, branded under the world-famous 'Mueller' name, to specification EN12735-1.

The tube is supplied in straight length sizes from 3/8" up to 1.3/8" diameter, and in coils in sizes from 1/4" up to 7/8" diameter.

The tube has been specially cleaned and nitrogen charged to render it suitable for HVAC and refrigeration purposes. Charging with nitrogen protects against the formation of harmful oxides during the brazing operation.

After cleaning, all tubes are individually end-capped to ensure their internal cleanliness. Soft coils are further protected by shrink-wrapping and packing them in individual cardboard cartons. The straight lengths are bundled and polythene wrapped.

Mueller Europe Ltd
Oxford Street, Bilston, WV14 7DS
T: +44 (0) 1902 499700, F: +44 (0) 1902 405838
E: sales@muellereurope.com
W: www.muellereurope.com





## **PRODUCT RANGE**



### **ACR SOFT COILS TO EN 12735-1 (R220)**

| Product Code | Size<br>OD | Wall<br>SWG | Wall<br>Inches | Length<br>metres | Temper | Coil Nos<br>per Box | Coils per<br>pallet | Maximum safe<br>working<br>pressure at<br>100°C (bar) |
|--------------|------------|-------------|----------------|------------------|--------|---------------------|---------------------|---|
| RC 014 22 06 | 1/4        | 22          | 0.028          | 6                | R220   | 7                   | 420                 | 100   |
| RC 014 22 15 | 1/4        | 22          | 0.028          | 15               | R220   | 8                   | 448                 | 100   |
| RC 014 22 30 | 1/4        | 22          | 0.028          | 30               | R220   | 8                   | 224                 | 100   |
| RC 516 20 06 | 5/16       | 20          | 0.036          | 6                | R220   | 6                   | 360                 | 103   |
| RC 516 20 15 | 5/16       | 20          | 0.036          | 15               | R220   | 6                   | 336                 | 103   |
| RC 516 20 30 | 5/16       | 20          | 0.036          | 30               | R220   | 6                   | 168                 | 103   |
| RC 038 21 06 | 3/8        | 21          | 0.032          | 6                | R220   | 5                   | 300                 | 74  |
| RC 038 21 15 | 3/8        | 21          | 0.032          | 15               | R220   | 5                   | 280                 | 74  |
| RC 038 21 30 | 3/8        | 21          | 0.032          | 30               | R220   | 4                   | 72                  | 74  |
| RC 012 21 06 | 1/2        | 21          | 0.032          | 6                | R220   | 8                   | 448                 | 54  |
| RC 012 21 15 | 1/2        | 21          | 0.032          | 15               | R220   | 4                   | 224                 | 54  |
| RC 012 21 30 | 1/2        | 21          | 0.032          | 30               | R220   | 3                   | 54                  | 54  |
| RC 058 20 06 | 5/8        | 20          | 0.036          | 6                | R220   | 6                   | 336                 | 48  |
| RC 058 20 15 | 5/8        | 20          | 0.036          | 15               | R220   | 6                   | 90                  | 48  |
| RC 058 20 30 | 5/8        | 20          | 0.036          | 30               | R220   | 3                   | 45                  | 48  |
| RC 034 19 06 | 3/4        | 19          | 0.040          | 6                | R220   | 5                   | 280                 | 45  |
| RC 034 19 15 | 3/4        | 19          | 0.040          | 15               | R220   | 2                   | 36                  | 45  |
| RC 034 19 30 | 3/4        | 19          | 0.040          | 30               | R220   | 2                   | 36                  | 45  |
| RC 078 19 15 | 7/8        | 19          | 0.040          | 15               | R220   | 2                   | 30                  | 38  |

Mueller Europe Ltd Oxford Street, Bilston, WV14 7DS

T: +44 (0) 1902 499700, F: +44 (0) 1902 405838

E: sales@muellereurope.com W: www.muellereurope.com





# REFRIGERATION STRAIGHT LENGTHS TO EN12735-1 (R250)



| Product Code | Size<br>OD | Wall<br>SWG | Wall<br>Inches | Length<br>metres | Temper | Lengths<br>per Hand<br>Bundle | Lengths per<br>Master<br>Bundle | Maximum safe<br>working<br>pressure at<br>100°C (bar) |
|--------------|------------|-------------|----------------|------------------|--------|-------------------------------|---------------------------------|---|
| RL 038 21 03 | 3/8        | 21          | 0.032          | 3                | R250   | 10                            | 500                             | 110   |
| RL 038 21 06 | 3/8        | 21          | 0.032          | 6                | R250   | 10                            | 400                             | 110   |
| RL 012 20 03 | 1/2        | 20          | 0.036          | 3                | R250   | 10                            | 500                             | 91  |
| RL 012 20 06 | 1/2        | 20          | 0.036          | 6                | R250   | 10                            | 250                             | 91  |
| RL 058 20 03 | 5/8        | 20          | 0.036          | 3                | R250   | 10                            | 300                             | 71  |
| RL 058 20 06 | 5/8        | 20          | 0.036          | 6                | R250   | 10                            | 200                             | 71  |
| RL 034 19 03 | 3/4        | 19          | 0.040          | 3                | R250   | 10                            | 300                             | 66  |
| RL 034 19 06 | 3/4        | 19          | 0.040          | 6                | R250   | 10                            | 150                             | 66  |
| RL 034 18 03 | 3/4        | 18          | 0.048          | 3                | R250   | 10                            | 250                             | 80  |
| RL 034 18 06 | 3/4        | 18          | 0.048          | 6                | R250   | 10                            | 100                             | 80  |
| RL 078 18 03 | 7/8        | 18          | 0.048          | 3                | R250   | 10                            | 150                             | 68  |
| RL 078 18 06 | 7/8        | 18          | 0.048          | 6                | R250   | 10                            | 100                             | 68  |
| RL 118 18 03 | 1.1/8      | 18          | 0.048          | 3                | R250   | 5                             | 100                             | 52  |
| RL 118 18 06 | 1.1/8      | 18          | 0.048          | 6                | R250   | 5                             | 90                              | 52  |
| RL 118 16 03 | 1.1/8      | 16          | 0.064          | 3                | R250   | 5                             | 100                             | 71  |
| RL 118 16 06 | 1.1/8      | 16          | 0.064          | 6                | R250   | 5                             | 60                              | 71  |
| RL 118 14 06 | 1.1/8      | 14          | 0.080          | 6                | R250   | 5                             | 50                              | 90  |
| RL 138 18 03 | 1.3/8      | 18          | 0.048          | 3                | R250   | 5                             | 100                             | 42  |
| RL 138 18 06 | 1.3/8      | 18          | 0.048          | 6                | R250   | 5                             | 70                              | 42  |
| RL 138 16 03 | 1.3/8      | 16          | 0.064          | 3                | R250   | 5                             | 100                             | 57  |
| RL 138 16 06 | 1.3/8      | 16          | 0.064          | 6                | R250   | 5                             | 50                              | 57  |
| RL 138 14 06 | 1.3/8      | 14          | 0.080          | 6                | R250   | 5                             | 40                              | 72  |
| RL 138 12 06 | 1.3/8      | 12          | 0.104          | 6                | R250   | 5                             | 30                              | 96  |

**Mueller Europe Ltd** 

Oxford Street, Bilston, WV14 7DS

T: +44 (0) 1902 499700, F: +44 (0) 1902 405838

E: sales@muellereurope.com W: www.muellereurope.com





## **PRODUCT MARKING**



The tubes are marked:

#### Soft (R220)

MEL EN12735-1R220 Size mm (Size inch) x wall mm (wall SWG) DDMMYY

#### Half-hard (R250)

MEL EN12735-1R250 HH Size mm (Size inch) x wall mm (wall SWG) DDMMYY

## **MECHANICAL PROPERTIES**

| Material<br>EN1173 | Temper<br>Common<br>Term | Tensile Strength<br>RM MPA min | Elongation A % min | Hardness (indicative) HV5 VPN |
|--------------------|--------------------------|--------------------------------|--------------------|-------------------------------|
| R220               | Soft                     | 220                            | 40                 | (40-70)                       |
| R250               | Half Hard                | 250                            | 30                 | (75-100)                      |

Mueller Europe Ltd Oxford Street, Bilston, WV14 7DS

T: +44 (0) 1902 499700, F: +44 (0) 1902 405838

E: sales@muellereurope.com W: www.muellereurope.com



